



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

PART MUST INSERT FULLY TO SURFACE A IN RECOMMENDED GRID



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	0.175 ohms max
D.C. RESISTANCE	4-6 @20°C	0.140 ohms max
D.C. RESISTANCE	12-10 @20°C	0.090 ohms max
INDUCTANCE	4-6 10kHz, 100mVAC, Ls	320uH ±10%
DIELECTRIC	1-12 tie(3+4), 1250VAC, 1 second	
URNS RATIO	(4-6):(1-3)	14.667:1, ±2%
URNS RATIO	(4-6):(12-10)	14.667:1, ±2%



Wire insulation & RoHS status not affected by wire color.
 Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: Tray PKG-0253 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.001 [.03]	DRAWING TITLE PFC INDUCTOR	PART NO. 750341239
00	9/11	SEE REVISION SHEET FOR REVISION LEVEL	CONVENTION PLACEMENT	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750341239	SPECIFICATION SHEET 1 OF 1