

AFE4400 and AFE4490 SPO2 Front End Demonstration Kit

Message Communication Protocol v3.0



Message Communication Protocol for AFE4400 / AFE4490 EVM

This document describes the message communication protocol for AFE4400 / AFE4490 EVM. The message communication protocol applies to AFE4400 / AFE4490 EVM with firmware revision 1.3 or higher in conjunction with AFE44x0SPO2EVM GUI version 2.0 or higher.

Command Format

1. Write Register Command

PC to EVM: 0x02 <2 bytes of ASCII addr with MSB first> <6 bytes of ASCII data with MSB first> 0x0D
e.g, to write a value of 0x456789 to address 0x12, the message format is

Byte Number	1	2	3	4	5	6	7	8	9	10
Description	Write Reg Command	ASCII addr MSB	ASCII addr LSB	ASCII data MSB	ASCII data	ASCII data	ASCII data	ASCII data	ASCII data LSB	End of packet
Payload	0x02	0x31	0x32	0x34	0x35	0x36	0x37	0x38	0x39	0x0D

2. Read Register Command:

PC to EVM: 0x03 <2 bytes of ASCII addr with MSB first> 0x0D
e.g, to read address 0x12, the message format is

Byte Number	1	2	3	4
Description	Read Reg Command	ASCII addr MSB	ASCII addr LSB	End of packet
Payload	0x03	0x31	0x32	0x0D

EVM to PC: 0x03 0x02 <3 bytes of raw data with LSB first> 0x03 0x0D
e.g, if the data read is 0x456789, the message format is

Byte Number	1	2	3	4	5	6	7
Description	Read Reg Command	Start of data	Raw data LSB	Raw data	Raw data MSB	End of data	End of packet
Payload	0x03	0x02	0x89	0x67	0x45	0x03	0x0D

3. Start Read ADC Register Command:

PC to EVM: 0x01 0x2A <4 bytes of N packets with MSB first> 0x0D

Example1: to capture 1024 packets, PC sends: "0x01 0x2A 0x00 0x00 0x04 0x00 0x0D"

The message format is

Byte Number	1	2	3	4	5	6	7
Description	Start Read ADC Reg Command	Dummy Data	Packet count MSB	Packet count	Packet count	Packet count LSB	End of packet
Payload	0x01	0x2A	0x00	0x00	0x04	0x00	0x0D

Example2: to capture 70000 packets, PC sends: "0x01 0x2A 0x00 0x01 0x11 0x70 0x0D"

Byte Number	1	2	3	4	5	6	7
Description	Start Read ADC Reg Command	Dummy Data	Packet count MSB	Packet count	Packet count	Packet count LSB	End of packet
Payload	0x01	0x2A	0x00	0x01	0x11	0x70	0x0D

For continuous data, PC sends 0 as the number of the packets.

Example: to capture continuous data, PC sends: "0x01 0x2A 0x00 0x00 0x00 0x00 0x0D"

Byte Number	1	2	3	4	5	6	7
Description	Start Read ADC Reg Command	Dummy Data	Packet count MSB	Packet count	Packet count	Packet count LSB	End of packet
Payload	0x01	0x2A	0x00	0x00	0x00	0x00	0x0D

EVM sends N packets with each packet having the following format:

EVM to PC: 0x01 0x02 <18 bytes of 6 channel data with LSB first> 0x03 0x0D

Byte Number	1	2	3	4	5	6	7	8
Description	Start Read ADC Reg Command	Start of data	LED2 data LSB	LED2 data	LED2 data MSB	LED2AMB data LSB	LED2AMB data	LED2AMB data MSB
Payload	0x01	0x02						

Byte Number	9	10	11	12	13	14	15	16
Description	LED1 data LSB	LED1 data	LED1 data MSB	LED1AMB data LSB	LED1AMB data	LED1AMB data MSB	LED2 – LED2AMB data LSB	LED2 – LED2AMB data
Payload								0x38

Byte Number	17	18	19	20	21	22
Description	LED2 – LED2AMB data MSB	LED1 – LED1AMB data LSB	LED1 – LED1AMB data	LED1 – LED1AMB data MSB	End of data	End of packet
Payload					0x03	0x0D

4. Stop Read ADC Register Command:

PC to EVM: 0x06 0x0D

Note: Clear the USB/ COM port buffer before a Start Read ADC Register command is issued.

Byte Number	1	2
Description	Stop Read ADC Reg Command	End of packet
Payload	0x06	0x0D

5. Device Identification Command:

PC to EVM: 0x04 0x0D

Byte Number	1	2
Description	Device Identification Command	End of packet
Payload	0x04	0x0D

AFE4400SPO2EVM to PC: 0x04 0x02 0x34 0x34 0x30 0x30 0x03 0x0D

Byte Number	1	2	3	4	5	6	7	8
Description	Device Identification Command	Start of data	ASCII byte	ASCII byte	ASCII byte	ASCII byte	End of data	End of packet
Payload	0x04	0x02	0x34	0x34	0x30	0x30	0x03	0x0D

AFE4490SPO2EVM to PC: 0x04 0x02 0x34 0x34 0x39 0x30 0x03 0x0D

Byte Number	1	2	3	4	5	6	7	8
Description	Device Identification Command	Start of data	ASCII byte	ASCII byte	ASCII byte	ASCII byte	End of data	End of packet
Payload	0x04	0x02	0x34	0x34	0x39	0x30	0x03	0x0D

6. Firmware Upgrade Command:

PC to EVM: 0x05 0x0D

After the GUI issues the command, the PC invokes user interactive executable to upgrade the firmware.

Byte Number	1	2
Description	Firmware Upgrade Command	End of packet
Payload	0x05	0x0D

7. Firmware Revision Command:

PC to EVM: 0x07 0x0D

Byte Number	1	2
Description	Firmware Revision Command	End of packet
Payload	0x07	0x0D

EVM to PC: 0x07 0x02 FW_MAJOR FW_MINOR 0x03 0x0D

E.g., for rev 1.3,
FW_MAJOR 1
FW_MINOR 3

Byte Number	1	2	3	4	5	6
Description	Firmware Revision Command	Start of data	ASCII byte	ASCII byte	End of data	End of packet
Payload	0x07	0x02	0x01	0x03	0x03	0x0D