



GPIO20: For Over current to ASM3242
GPIO20

0: Normal, 1: Over Current

GPIO21: Indicator for configuration channel when device attached on CC1or CC2 output to ASM3242

GPIO21

0: CC1, 1: CC2

GPIO12/13: Indicator for device attached on CC1or CC2 output to ASM3242

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

GPIO12 GPIO13

0 1 0 3A 2.2A

RESEARCH & DEVELOPMENT DEPT.

Approve by: **JACKY**

Monday, February 24, 2020

Model: **UB-159**

Sheet 5 of 5

LYCOM TECHNOLOGY INC.,

USB PD

Size	CAGE Code	DWG NO	Rev
A3			00A