



The size 1210 capacitor have a special footprint where each endcap has two connections; an "inboard side" and an "outboard side." This permits the schematic to enforce input or output current flow directly past the endcap of the capacitors

The schematic parts inside the dotted box are inboard. None of these devices connect to ground or to any net outside of the box.

If a net needs to cross the boundary, it should do so through a resistor that straddles the dividing line

For clarity, other required passives are not included in this schematic

Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

TID #:	N/A	Designed for:	E2E Forum Release	Mod. Date:	8/30/2016
Number:	E2E_ABCD	Rev:	E1	Project Title:	LMZ31506 Low EMI Layout Example
SVN Rev:	Version control disabled	Assembly Variant:	001	Sheet:	2 of 3
Drawn By:		File:	LMZ_Layout_Example.SchDoc	Size:	Letter
Engineer:	Alan Martin	Contact:	http://www.ti.com/support		

 **TEXAS INSTRUMENTS**
<http://www.ti.com>
 © Texas Instruments 2016