



| MODE SELECTION | ACTION | R _{MODE} (kΩ) | R-C TIME CONSTANT (μs) | SWITCHING FREQUENCIES f _{sw} (kHz) |
|---------------------|------------------|------------------------|------------------------|---|
| Skip Mode | Pull down to GND | 0 | 60 | 250 and 300 |
| | | | 50 | 400 and 500 |
| | | | 40 | 600 and 750 |
| | | | 30 | 850 and 1000 |
| | | | 120 | 250 and 300 |
| FCCM ⁽¹⁾ | Connect to PGOOD | 150 | 100 | 400 and 500 |
| | | | 80 | 600 and 750 |
| | | | 60 | 850 and 1000 |
| | | | 60 | 250 and 300 |
| | | | 50 | 400 and 500 |
| FCCM | Connect to VREG | 20 | 40 | 600 and 750 |
| | | | 30 | 850 and 1000 |
| | | | 120 | 250 and 300 |
| | | | 100 | 400 and 500 |
| | | | 80 | 600 and 750 |
| FCCM | Connect to VREG | 150 | 60 | 850 and 1000 |
| | | | 120 | 250 and 300 |
| | | | 100 | 400 and 500 |
| FCCM | Connect to VREG | 0 | 80 | 600 and 750 |
| | | | 60 | 850 and 1000 |
| | | | 60 | 850 and 1000 |

Webench specified 0.1ohm Rmode. However, it is a value not included in the recommended value of the data sheet. Please tell me the reason.