



ADS52J90 8/16/32-Channel, Analog-to-Digital Converter Evaluation Module

This user's guide gives an overview of the evaluation module (EVM) and provides a general description of the features and functions to be considered while using this module. This manual is applicable to the ADS52J90 analog-to-digital converters (ADC). The ADS52J90 EVM provides a platform for evaluating the ADC under various signal, clock, reference, and ADC output formats. In addition, the EVM supports the testing of both an LVDS interface as well as a JESD204B interface.

NOTE: A different capture card EVM is required for each.

Contents

1	Quick Views of Evaluation Setups for LVDS and JESD204B Interfaces	3
1.1	LVDS Interface (ADS52J90 EVM + TSW1400).....	3
1.2	JESD204B Interface (ADS52J90 EVM + TSW14J56)	4
2	GUI Software Installation	5
2.1	High Speed Data Converter Pro (HSDCpro) GUI Installation	5
2.2	ADS52J90 GUI Installation (HMC-DAQ).....	5
3	ADS52J90 EVM Headers/Test Points and Clock Configuration.....	6
3.1	ADS52J90 EVM Header Configuration	6
3.2	ADS52J90 EVM Test points.....	7
3.3	EVM Clock Configuration	8
4	Quick Test LVDS Interface	9
4.1	EVM Layout and Hardware Setup.....	9
4.2	Capturing Ramp Test Pattern and Sinusoidal Input	12
4.3	Testing All Modes of the Device.....	24

List of Figures

1	LVDS Evaluation Setup	3
2	JESD204B Evaluation Setup	4
3	Clock Config: LMK CDM Mode	8
4	HSDCpro 40x Lane Rate Message	9
5	HSDCpro 10x Lane Rate Message	9
6	ADS52J90 EVM Analog Channels	10
7	TSW1400 and ADS52J90 Setup	11
8	TSW1400 GUI Setup (a)	12
9	TSW1400 GUI Setup (b)	13
10	TSW1400 GUI Setup (c)	13
11	TSW1400 GUI Setup (d)	14
12	TSW1400 GUI Setup (e)	14
13	TSW1400 GUI Setup (f)	15
14	HMC-DAQ GUI Setup (a)	15
15	HMC-DAQ GUI Setup (b)	16

16	HMC-DAQ GUI Setup (c)	16
17	HMC-DAQ GUI Setup (d)	17
18	ADS52J90 16-Channel RAMP Capture (a)	18
19	ADS52J90 16-Channel RAMP Capture (b)	19
20	ADS52J90 16-Channel RAMP Capture (c)	19
21	ADS52J90 16-Channel RAMP Capture (d)	20
22	ADS52J90 16-Channel SINE Capture (a)	21
23	ADS52J90 16-Channel SINE Capture (b)	22
24	ADS52J90 16-Channel SINE Capture (c)	23
25	ADS52J90 All Supported Configs	24
26	ADS52J90 All Supported Configs (b)	25
27	ADS52J90 All Supported Configs (c)	26

List of Tables

1	ADS52J90 Default Header Configuration.....	6
2	ADS52J90 EVM Test Points	7

1 Quick Views of Evaluation Setups for LVDS and JESD204B Interfaces

The ADS52J90 EVM can be tested using an LVDS data interface or a JESD204B data interface.

1.1 LVDS Interface (ADS52J90 EVM + TSW1400)

As shown in Figure 1, mating the ADS52J90 EVM with a TSW1400 EVM allows testing using an LVDS data interface.




Figure 1. LVDS Evaluation Setup

FPGA EVM: The TSW1400 high-speed LVDS de-serializer EVM is required for capturing data from the ADS52J90EVM. Analysis of the captured data is possible using its graphical user interface (GUI) which is called High Speed Data Converter Pro.

NOTE: The same GUI is used to control the TSW14J56 capture card for supporting a JESD204B data interface.

For more information pertaining to the TSW1400EVM, see:
<http://focus.ti.com/docs/toolsw/folders/print/tsw1400evm.html>.

Equipment: Signal generators (with low-phase noise) must be used as source of input signal and clock in order to get the desired performance. Additionally, a band-pass filter (BPF) is required on the analog input signal to attenuate the harmonics and noise from the generators.

Power Supply: A single +5-V supply powers the ADS52J90EVM through connectors located at **J47** and **J48** or through an AC adaptor (not provided) at **J46**. The supply for the ADS52J90 device is derived from this +5-V supply. The power supply must be able to source up to 1.5 A. The TSW1400 EVM is powered through an AC adaptor provided with its EVM kit.

USB Interface to PC: The USB connections from the ADS52J90EVM and TSW1400EVM to the computer are used for communication from the GUIs to the boards. [Section 2](#) explains the *High Speed Data Converter Pro* and ADS52J90 GUI installation procedures.

1.2 JESD204B Interface (ADS52J90 EVM + TSW14J56)

As shown in [Figure 2](#), mating the ADS52J90 EVM with a TSW14J56 EVM allows testing using a JESD204B data interface.




Figure 2. JESD204B Evaluation Setup

FPGA EVM: The TSW14J56 high-speed JESD204B de-serializer board is required for capturing data from the ADS52J90EVM. Analysis of the captured data is possible using its graphical user interface (GUI) which is called High Speed Data Converter Pro (*note: the same GUI is used to control the TSW1400 capture card for supporting an LVDS data interface*).

For more information pertaining to the TSW14J56EVM, see: <http://www.ti.com/tool/tsw14j56evm>

Equipment: Signal generators (with low-phase noise) must be used as source of input signal and clock in order to get the desired performance. Additionally, a band-pass filter (BPF) is required on the analog input signal to attenuate the harmonics and noise from the generator.

Power Supply: A single +5-V supply powers the ADS52J90EVM through connectors located at **J47** and **J48** or through an AC adaptor (not provided) at **J46**. The supply for the ADS52J90 device is derived from this +5-V supply. The power supply must be able to source up to 1.5 A. The TSW14J56 EVM is powered through an AC adaptor provided with its EVM kit.

USB Interface to PC: The USB connections from the ADS52J90EVM and TSW14J56EVM to the computer are used for communication from the GUIs to the boards. [Section 2](#) explains the *High Speed Data Converter Pro* and ADS52J90 GUI installation procedures.

2 GUI Software Installation

The ADS52J90 EVM and the de-serializing capture card EVM both require software installations. The following two sections explain where to find and how to install the software properly. Ensure that no USB connections are made to the EVMs until after the installations are complete.

2.1 High Speed Data Converter Pro (HSDCpro) GUI Installation

Download the [High Speed Data Converter Pro GUI Installer \(SLWC107\)](#) from the Texas Instruments website (www.ti.com) and install per the instructions in its user's guide ([SLWU087](#)).

NOTE: Version 3.1 or higher of HSDC Pro is required to test the ADS52J0. If an earlier version of HSDC Pro is installed, please uninstall before installing the latest version.

TI recommends installing HSDC Pro before installing the ADS52J90 GUI and installing it in the default location provided during installation.

2.2 ADS52J90 GUI Installation (HMC-DAQ)

The GUI used to control the ADS52J90 EVM is a suite that supports a family of devices. The GUI is called *Healthtech Multi-Channel Data Acquisition GUI*, or, *HMC-DAQ*. Download and save the file *HMC-DAQ_GUI_INSTALLER_SLOC326.zip* to a temporary location on the local PC hard drive. Once saved, unzip the file and run the executable as administrator by right clicking on the file. Follow the instructions provided during installation. TI recommends installing after HSDCpro has been installed and in the default location provided during installation.

3 ADS52J90 EVM Headers/Test Points and Clock Configuration

This section describes the functions of the headers on the EVM. It also provides a list of test points on the EVM that are useful for debug and general-use purposes. Finally, several options for providing clocks to the EVM are described.

3.1 ADS52J90 EVM Header Configuration

The ADS52J90 EVM is flexible in its configurability through the use of 2- and 3-pin headers. [Table 1](#) describes the purpose of all headers on the EVM and the default positions. With this configuration, all required clocks for testing the LVDS or JESD204B interface are derived from a single reference clock provided to SMA J75 to the LMK04826 clocking device installed at designator **U2** on the EVM. The LMK04826 is configured for Clock Distribution Mode (CDM) with the provided scripts.

Table 1. ADS52J90 Default Header Configuration

Jumper Description	Jumper#	Jumper Name	Default Config	Circuit	Description
Power Supply	JP9	+3.3VCLK	Short pins 1-2	Clocks	Power supply XTAL1, XTAL2, OSC1, LMK04826
	JP10	IOVDD_+3.3V	Short pins 1-2	SPI BUFFERS	Power supply for SPI level shifters and isolators
	JP11	DVDD_+1.2V	Short pins 1-2	ADS52JD90	+1.2-V digital power supply for ADS52JD90
	JP12	AVDD_+1.8V	Short pins 1-2	ADS52JD90	+1.8-V analog power supply for ADS52JD90
	JP13	LVDD_+1.8V	Short pins 1-2	ADS52JD90	+1.8-V digital power supply for ADS52JD90
	JP15	DISABLE	DNI	Regulator	Not used
	JP16	5VIN	DNI	Regulator	Not used
ADS52J90 SYNC Options	JP33	n/a	Short pins 1-2	ADS52JD90 SYNC pin	Selects SYNC signal source to ADS52JD90: (1) Auxiliary signal determined by JP28 or (3) GUI via FTDI device
	JP28	n/a	Short pins 1-2	ADS52JD90 SYNC pin	Selects auxiliary SYNC signal source to ADS52JD90: (1) SMA J50 or (3) FPGA via pin 105 of connector J44B
LMK04826 Options	JP2	SYNC	Short pins 1-2	LMK SYNC	Selects the source of SYNC signal into LMK042x clock device: (1) signal from SMA J39, LMK_SYNC or (3) signal from FPGA at pin K22 of connector J43C
	JP3	LMK_RB	Short pins 2-3	LMK Readback/Reset	Selects LMK RESET pin signal source: (1) LMK_DATA_OUT out to FTDI (3) LMK_RESET in from FTDI
ADC_CLKP/M SEL	JP39	ADC_CLK_AUX	Short pins 1-2	ADS52J90 CLKP/M & SYSREFP/M Source	Selects auxiliary CLKP/M signal source to ADS52JD90: (1) SMA J55, ADC_CLK or (3) one of two on-board XTAL oscillators determined by JP8
	JP40	ADC_CLK	Short pins 2-3		Selects signal source to CLKP/M of ADS52J90: (1) Auxiliary source from JP39 or (3) LMK04826 output
	JP41	ADC_SYSREF	Short pins 1-2		Selects signal source to CLKP/M of ADS52J90: (1) Auxiliary source from JP39 or (3) LMK04826 output
XTAL Power Supply Options	JP4	OSC1_VDD	Open	XTAL/OSC Power	Powers 100-MHz OSC1
	JP5	XTAL1_VDD	Open		Powers 10-MHz XTAL1
	JP6	XTAL2_VDD	Open		Powers 40-MHz XTAL2
XTAL SEL	JP7	LMK_CLKIN1	Short pins 1-2	LMK CLKIN1	Selects signal source to CLKIN1 of LMK04826: (1) SMA J75, LMK_CLKIN1 or (3) XTAL determined by JP8
	JP8	XTAL_SEL	Open	XTAL Oscillators	Selects XTAL source to JP7 and JP39: (1) 10MHz XTAL1 or (3) 40MHz XTAL2
Analog Inputs 8ch mode	JP700_7	n/a	Short pins 2-3	Analog Inputs 8ch mode	Selects between (1) 5-V power supply and (2) and GND for amplifier on channels 7,8 for 8ch mode
	JP800_8	n/a	Short pins 2-3		

Jumpers **JP11**, **JP12**, **JP13** can be removed and individual power supplies given to these headers in order to monitor the DC current consumed by the ADS52J90.

3.2 ADS52J90 EVM Test points

Table 2 lists all test points on the ADS52J90 EVM and their purposes.

Table 2. ADS52J90 EVM Test Points

Test Point	Silkscreen	Circuit	Description
TP13	+5.0V_IN	Power supply	Main +5-V power supply to EVM
TP15	GND	Power supply	Ground reference for EVM
TP14	IOVDD3.3V	Power supply	Power supply for VCM generation
TP12	+3.3VCLK	Power supply	Power supply for LMK0482x and oscillators
TP16	4V	Power supply	Input supply to regulator at designator U11
TP17	AVDD_+1.8V	Power supply	Power supply to ADS52J90
TP18	LVDD_+1.8V	Power supply	Power supply to ADS52J90
TP19	FORCE_VCM	Analog inputs	Can provide external VCM to analog inputs by installing R108 and uninstalling R110
TP20	FORCE_VREF	Analog inputs	Can provide external VREF to ADS52J90 by installing R109
TP1	VCM	Analog inputs	ADS52J90 output providing VCM to analog inputs
TP4	GTx_CLKP	LMK0428x output	GTx clock to FPGA on capture card
TP5	GTx_CLKM	LMK0428x output	GTx clock to FPGA on capture card
TP21	CLK_LAO_0P	LMK0428x output	Global clock to FPGA on capture card (typ. equals Fs)
TP22	CLK_LAO_0M	LMK0428x output	Global clock to FPGA on capture card (typ. equals Fs)
TP6	SYSREF_P	LMK0428x output	SYSREF clock to FPGA on capture card
TP7	SYSREF_M	LMK0428x output	SYSREF clock to FPGA on capture card
TP8	CLKP	LMK0428x output	Device clock (Fs) to DUT from LMK0482x
TP10	CLKM	LMK0428x output	Device clock (Fs) to DUT from LMK0482x
TP9	SYSREFP	LMK0428x output	SYSREF clock to DUT from LMK0482x
TP11	SYSREFM	LMK0428x output	SYSREF clock to DUT from LMK0482x
TP37	CLK_P	DET LAT EVM	Device clock (Fs) to DUT when Deterministic Latency EVM is used
TP38	CLK_M	DET LAT EVM	Device clock (Fs) to DUT when Deterministic Latency EVM is used
TP35	SYSREF_P	DET LAT EVM	SYSREF clock to DUT when Deterministic Latency EVM is used
TP36	SYSREF_M	DET LAT EVM	SYSREF clock to DUT when Deterministic Latency EVM is used
TP23	GND	GND	Ground reference for EVM
TP2	SYNCP_SERDES	JESD SYNC	Input JESD SYNC~ to ADS52J90 from FPGA
TP3	SYNCM_SERDES	JESD SYNC	Input JESD SYNC~ to ADS52J90 from FPGA
TPA0	SCLK	ADS52J90 SPI PIN	SPI clock input to ADS52J90
TPA1	SDATA	ADS52J90 SPI PIN	SPI data input to ADS52J90
TPA2	SEN	ADS52J90 SPI PIN	SPI enable input to ADS52J90
TPA3	SDOUT	ADS52J90 SPI PIN	SPI read back output from ADS52J90
TPA4	RESET	ADS52J90 PIN	RESET pin to ADS52J90
TPA5	PDN_GBL	ADS52J90 PIN	PDN_GBL pin of ADS52J90
TPA6	PDN_FAST	ADS52J90 PIN	PDN_FAST pin of ADS52J90
TPA7	SYNC_LVDS_FTDI	ADS52J90 PIN	SYNC pin to ADS52J90 allowing for synchronized LVDS outputs
TPB0	LMK_CLK	LMK SPI PIN	SPI clock input to LMK0482x
TPB1	LMK_DATA_OUT	LMK SPI PIN	SPI read back output from LMK0482x
TPB2	LMK_DATA	LMK SPI PIN	SPI data input to LMK0482x
TPB3	LMK_SPI_EN	LMK SPI PIN	SPI enable input to LMK0482x
TPB4	LMK_RESET	LMK PIN	RESET pin to LMK0482x
TPB5	RSV_DIG	n/a	Reserved
TP24	GND	GND	Ground Reference for EVM

3.3 EVM Clock Configuration

The EVM should be shipped with jumpers setting the LMK04826 clocking device (U2) in clock distribution mode. In this configuration shown in [Figure 3](#), the LMK04826 acts as a clock buffer/divider on the external input clock to SMA **J75, LMK_CLKIN1**. For LVDS mode, this input clock should be set to the desired system clock required by the ADS52J90. To support the JESD204B interface, this input clock should be set to 1/40 the SerDes line rate when the line rate is above 1Gbps and 1/10 the SerDes line rate when the line rate is below 1Gbps. Put another way, the SerDes lane rate will be 10x the reference clock when the calculated lane rate is below 1Gbps and will be 40x the reference clock when the calculated lane rate is above 1Gbps. The HSDCpro GUI will report both the calculated lane rate and the required reference clock each time the user changes the *Output Data Rate* value in the GUI. [Figure 4](#) and [Figure 5](#) show examples of the message when lane rate is 40x the reference clock and when the lane rate is 10x the reference clock, respectively. Configuration scripts for both 10x rate and 40x rate are provided in folders with the appropriate suffix appended to the folder names.




Figure 3. Clock Config: LMK CDM Mode




Figure 4. HSDCpro 40x Lane Rate Message




Figure 5. HSDCpro 10x Lane Rate Message

4 Quick Test LVDS Interface

This section outlines the following:

- EVM Layout and Hardware Setup
- How to capture a RAMP and Sinusoidal Inputs for 16ch mode
- How to use scripts to measure all LVDS modes supported by the device

4.1 EVM Layout and Hardware Setup

The ADS52J90 supports 3 modes of operation with respect to the analog inputs: (1) 32-channel mode, (2) 16-channel mode, (3) 8-channel mode. [Figure 6](#) shows the breakdown of the analog channels on the EVM. Testing 32-channel mode is done using all Channels 1-24 on the EVM. Testing 16-channel mode is done using the odd channels of 1-23 on the EVM. These are the vertically-mounted SMAs. Testing 8-channel mode is done using Channels 7 and 8. Channel 7 is configured to accept a differential input to **SMA_CH7A** and **SMA_CH7** whereas Channel 8 is configured to convert a signal ended input to **SMA_CH8** into a differential signal via an amplifier.




Figure 6. ADS52J90 EVM Analog Channels

The connections shown in [Figure 7](#) should be made for proper hardware setup.

NOTE: Testing the LVDS interface between the ADS52J90 EVM and the TSW1400 EVM can be performed using a RAMP test pattern generated within the ADS52J90 device in lieu of the signal source listed in item 7, in the following steps.




Figure 7. TSW1400 and ADS52J90 Setup

1. Mate the TSW1400 EVM at connector J3 to the ADS52J90 EVM at connector **J44** through the high speed ADC interface connector.

NOTE: The two standoffs closest to J3 on the TSW1400 must be removed. Also, the EVM kit provides two supplementary standoffs that should be added to the remaining two standoffs so that the two EVMs are properly aligned.

2. Connect a DC +5-V power supply output of the provided AC-to-DC power supply to **J12 (+5V_IN)** of the TSW1400 EVM and the input of the power supply cable to a 110–230 VAC source.
3. Ensure that **SW7** is set to ON position on TSW1400.
4. Connect a DC +5-V power supply across banana jacks **J47** and **J48** on the ADS52J90 EVM. Alternatively, test points **TP13** and **TP15** can be used if alligator clip leads are available.
5. Connect the USB cable from the PC to **J45 (USB)** of the ADS52J90 EVM.
6. Connect the USB cable from the PC to **J5 (USB_IF)** of the TSW1400 EVM.

NOTE: TI recommends that the PC USB port be able to support USB2.0. If unsure, always chose the USB ports at the back of the PC chassis over ones located on the front or sides.

- Supply an analog input signal to SMA **J1 (SMA_CH1)** of the ADS52J90 EVM (such as +16 dBm, 5.0 MHz).

NOTE: A low phase noise signal source (such as R&S SMA100A) with a band pass filter is needed in order to measure SNR values reported in the datasheet. Also, the instrument should have a 10-MHz back panel reference port allowing for coherent sampling when phase locked with the sampling clock signal.

- Supply a reference clock to SMA **J75 (LMK_CLKIN1)** of the ADS52J90 EVM that is equal to the desired system clock frequency. In the following examples 65 MHz is used as it supports all channel modes of the device.

NOTE: A low phase noise, highly linear, signal source (such as RS SMA100A) is needed in order to measure SNR values reported in the datasheet. Also, the instrument should have a 10-MHz back panel reference port allowing for coherent sampling when phase locked with the analog input clock signal

4.2 Capturing Ramp Test Pattern and Sinusoidal Input

- With the hardware setup shown in [Figure 7](#) established, launch the *High Speed Data Converter Pro* GUI. The GUI should automatically detect the serial number of the TSW1400 EVM connected as shown in [Figure 8](#). Click on OK.




Figure 8. TSW1400 GUI Setup (a)

The message shown in [Figure 9](#) will appear. Click OK.




Figure 9. TSW1400 GUI Setup (b)

If instead, the message shown in [Figure 10](#) appears, it indicates that the USB connection to the TSW1400 EVM is not present. Click OK, then establish a USB connection and repeat [step 1](#).




Figure 10. TSW1400 GUI Setup (c)

2. Select a device firmware to load in the FPGA by clicking on the blue arrow in the upper left corner of the *HSDCpro* GUI. Scroll down and select *ADS52J90* as shown in [Figure 11](#).




Figure 11. TSW1400 GUI Setup (d)

Click the Yes button to update the ADC firmware on the TSW1400 FPGA as depicted in [Figure 12](#).




Figure 12. TSW1400 GUI Setup (e)

While the firmware is being loaded into the TSW1400 FPGA, the graphic shown in [Figure 13](#) will appear after which the device GUI (HMC-DAQ) will launch as shown in [Figure 14](#).




Figure 13. TSW1400 GUI Setup (f)




Figure 14. HMC-DAQ GUI Setup (a)

If the GUI recognizes that hardware is connected, HMC-DAQ will show HW CONNECTED in green in the border of the GUI as shown in [Figure 15](#).




Figure 15. HMC-DAQ GUI Setup (b)

If instead, the message shown in [Figure 16](#) appears, it indicates a USB connection issues between the PC and the ADS52J90 EVM. Close HSDCpro, establish USB connections and restart from [procedure 1](#).




Figure 16. HMC-DAQ GUI Setup (c)

3. At this point there should be two GUI's running and connected, HSDCpro and HMC-DAQ which are communicating behind the scenes. Anytime the ADS52J90 device configuration is updated, HSDCpro is informed and the appropriate firmware updates are done automatically. To capture a RAMP test pattern in LVDS, 16-channel, 14 bit, 14x serialization configuration, do the following as shown in Figure 17:
 - (a) Press **DUT RESET** button
 - (b) Press **Initialize Device** button
 - (c) Check the box next to **LVDS 16ch 14x 14b**
 - (d) Check the box next to **Ramp Test Pattern**




Figure 17. HMC-DAQ GUI Setup (d)

4. Return to HSDCpro GUI and perform the following steps as shown in [Figure 18](#) .
 - (a) Change the plot type from *Real FFT* to *Codes*
 - (b) Enter 65M in the field labeled *ADC Output Data Rate*
 - (c) Press the *Capture* button.




Figure 18. ADS52J90 16-Channel RAMP Capture (a)

A RAMP capture should appear as shown in Figure 19.




Figure 19. ADS52J90 16-Channel RAMP Capture (b)

By default, Ch1 (16CH) is the first channel displayed. Use the drop-down menu shown in Figure 20 to view any one 16 channels.




Figure 20. ADS52J90 16-Channel RAMP Capture (c)

Zooming into the waveform and changing the plot graphic (using the buttons to the upper right of graph), as shown in Figure 21, is recommended to confirm that the RAMP waveform is correct with each subsequent sample incremented 1 ADC code until max code of $(2^N) - 1$ is reached, where N is ADC resolution.




Figure 21. ADS52J90 16-Channel RAMP Capture (d)

- To capture a sinusoidal input, return to the HMC-DAQ GUI and press the check box next to **Analog Input** as shown in Figure 22.




Figure 22. ADS52J90 16-Channel SINE Capture (a)

6. Return to HSDCpro GUI and perform the following (as illustrated in Figure 23):
 - (a) Change the plot type from Codes to Real FFT
 - (b) Enter 65M in the field labeled ADC Output Data Rate
 - (c) Enter 5.0M in the field labeled ADC Input Target Frequency (or set to the desired input that is being provided to SMA J1, SMA_CH1, as described in (Section 4.1).
 - (d) Press the Capture button.




Figure 23. ADS52J90 16-Channel SINE Capture (b)

A capture similar to that shown in Figure 24 should appear.

NOTE: The analog input level was adjusted and a recapture done iteratively until the **Fund.** value was approximately -1 dBFs.




Figure 24. ADS52J90 16-Channel SINE Capture (c)

By default, *Ch1 (16CH)* is the first channel displayed. Use the drop-down menu to view any one 16 channels.

NOTE: The vertically-mounted SMAs on the EVM are the analog inputs to the odd ADC channels while the side-mounted SMAs are the analog inputs to the even ADC channels. Per the datasheet, only odd channels are being sampled when in 16-channel mode.

4.3 Testing All Modes of the Device

In addition to the quick start buttons provided on the **QUICK SETUP** tab of HMC-DAQ GUI, there are scripts to configure the device for all supported modes. To access the scripts, click on the folder icon in the upper left corner of the HMC-DAQ GUI, as shown in [Figure 25](#).




Figure 25. ADS52J90 All Supported Configs

Navigate to the folder/Scripts/ADS52J90/LVDS/LMK_CDM_MODE as shown in Figure 26.




Figure 26. ADS52J90 All Supported Configs (b)

Select anyone of 24 configurations provided and then press *Capture* in HSDCpro. When testing 32-channel mode, ensure that the **ADC Output Data Rate** in HSDCpro is set to half the system clock being provided to the device. For example, if 65 MHz is supplied to **J75** then this value should be set to 32.5 MHz. When testing 8-channel or 16-channel modes, the **ADC Output Data Rate** should be set to the value of the system clock provided to the DUT.




Figure 27. ADS52J90 All Supported Configs (c)

STANDARD TERMS AND CONDITIONS FOR EVALUATION MODULES

1. *Delivery:* TI delivers TI evaluation boards, kits, or modules, including any accompanying demonstration software, components, or documentation (collectively, an "EVM" or "EVMs") to the User ("User") in accordance with the terms and conditions set forth herein. Acceptance of the EVM is expressly subject to the following terms and conditions.

- 1.1 EVMs are intended solely for product or software developers for use in a research and development setting to facilitate feasibility evaluation, experimentation, or scientific analysis of TI semiconductors products. EVMs have no direct function and are not finished products. EVMs shall not be directly or indirectly assembled as a part or subassembly in any finished product. For clarification, any software or software tools provided with the EVM ("Software") shall not be subject to the terms and conditions set forth herein but rather shall be subject to the applicable terms and conditions that accompany such Software
- 1.2 EVMs are not intended for consumer or household use. EVMs may not be sold, sublicensed, leased, rented, loaned, assigned, or otherwise distributed for commercial purposes by Users, in whole or in part, or used in any finished product or production system.

- 2 *Limited Warranty and Related Remedies/Disclaimers:*

- 2.1 These terms and conditions do not apply to Software. The warranty, if any, for Software is covered in the applicable Software License Agreement.
- 2.2 TI warrants that the TI EVM will conform to TI's published specifications for ninety (90) days after the date TI delivers such EVM to User. Notwithstanding the foregoing, TI shall not be liable for any defects that are caused by neglect, misuse or mistreatment by an entity other than TI, including improper installation or testing, or for any EVMs that have been altered or modified in any way by an entity other than TI. Moreover, TI shall not be liable for any defects that result from User's design, specifications or instructions for such EVMs. Testing and other quality control techniques are used to the extent TI deems necessary or as mandated by government requirements. TI does not test all parameters of each EVM.
- 2.3 If any EVM fails to conform to the warranty set forth above, TI's sole liability shall be at its option to repair or replace such EVM, or credit User's account for such EVM. TI's liability under this warranty shall be limited to EVMs that are returned during the warranty period to the address designated by TI and that are determined by TI not to conform to such warranty. If TI elects to repair or replace such EVM, TI shall have a reasonable time to repair such EVM or provide replacements. Repaired EVMs shall be warranted for the remainder of the original warranty period. Replaced EVMs shall be warranted for a new full ninety (90) day warranty period.

- 3 *Regulatory Notices:*

- 3.1 *United States*

- 3.1.1 *Notice applicable to EVMs not FCC-Approved:*

This kit is designed to allow product developers to evaluate electronic components, circuitry, or software associated with the kit to determine whether to incorporate such items in a finished product and software developers to write software applications for use with the end product. This kit is not a finished product and when assembled may not be resold or otherwise marketed unless all required FCC equipment authorizations are first obtained. Operation is subject to the condition that this product not cause harmful interference to licensed radio stations and that this product accept harmful interference. Unless the assembled kit is designed to operate under part 15, part 18 or part 95 of this chapter, the operator of the kit must operate under the authority of an FCC license holder or must secure an experimental authorization under part 5 of this chapter.

- 3.1.2 *For EVMs annotated as FCC – FEDERAL COMMUNICATIONS COMMISSION Part 15 Compliant:*

CAUTION

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC Interference Statement for Class A EVM devices

NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

FCC Interference Statement for Class B EVM devices

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- *Reorient or relocate the receiving antenna.*
- *Increase the separation between the equipment and receiver.*
- *Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.*
- *Consult the dealer or an experienced radio/TV technician for help.*

3.2 Canada

3.2.1 For EVMs issued with an Industry Canada Certificate of Conformance to RSS-210

Concerning EVMs Including Radio Transmitters:

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Concernant les EVMs avec appareils radio:

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Concerning EVMs Including Detachable Antennas:

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication. This radio transmitter has been approved by Industry Canada to operate with the antenna types listed in the user guide with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Concernant les EVMs avec antennes détachables

Conformément à la réglementation d'Industrie Canada, le présent émetteur radio peut fonctionner avec une antenne d'un type et d'un gain maximal (ou inférieur) approuvé pour l'émetteur par Industrie Canada. Dans le but de réduire les risques de brouillage radioélectrique à l'intention des autres utilisateurs, il faut choisir le type d'antenne et son gain de sorte que la puissance isotrope rayonnée équivalente (p.i.r.e.) ne dépasse pas l'intensité nécessaire à l'établissement d'une communication satisfaisante. Le présent émetteur radio a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés dans le manuel d'usage et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur.

3.3 Japan

3.3.1 *Notice for EVMs delivered in Japan:* Please see http://www.tij.co.jp/llds/ti_ja/general/eStore/notice_01.page 日本国内に輸入される評価用キット、ボードについては、次のところをご覧ください。
http://www.tij.co.jp/llds/ti_ja/general/eStore/notice_01.page

3.3.2 *Notice for Users of EVMs Considered "Radio Frequency Products" in Japan:* EVMs entering Japan are NOT certified by TI as conforming to Technical Regulations of Radio Law of Japan.

If User uses EVMs in Japan, User is required by Radio Law of Japan to follow the instructions below with respect to EVMs:

1. Use EVMs in a shielded room or any other test facility as defined in the notification #173 issued by Ministry of Internal Affairs and Communications on March 28, 2006, based on Sub-section 1.1 of Article 6 of the Ministry's Rule for Enforcement of Radio Law of Japan,
2. Use EVMs only after User obtains the license of Test Radio Station as provided in Radio Law of Japan with respect to EVMs, or
3. Use of EVMs only after User obtains the Technical Regulations Conformity Certification as provided in Radio Law of Japan with respect to EVMs. Also, do not transfer EVMs, unless User gives the same notice above to the transferee. Please note that if User does not follow the instructions above, User will be subject to penalties of Radio Law of Japan.

【無線電波を送信する製品の開発キットをお使いになる際の注意事項】

本開発キットは技術基準適合証明を受けておりません。

本製品のご使用に際しては、電波法遵守のため、以下のいずれかの措置を取っていただく必要がありますのでご注意ください。

1. 電波法施行規則第6条第1項第1号に基づく平成18年3月28日総務省告示第173号で定められた電波暗室等の試験設備でご使用いただく。
2. 実験局の免許を取得後ご使用いただく。
3. 技術基準適合証明を取得後ご使用いただく。

なお、本製品は、上記の「ご使用にあたっての注意」を譲渡先、移転先に通知しない限り、譲渡、移転できないものとします。

上記を遵守頂けない場合は、電波法の罰則が適用される可能性があることをご留意ください。

日本テキサス・インスツルメンツ株式会社

東京都新宿区西新宿 6 丁目 2 4 番 1 号

西新宿三井ビル

3.3.3 *Notice for EVMs for Power Line Communication:* Please see http://www.tij.co.jp/llds/ti_ja/general/eStore/notice_02.page

電力線搬送波通信についての開発キットをお使いになる際の注意事項については、次のところをご覧ください。http://www.tij.co.jp/llds/ti_ja/general/eStore/notice_02.page

4 *EVM Use Restrictions and Warnings:*

4.1 EVMS ARE NOT FOR USE IN FUNCTIONAL SAFETY AND/OR SAFETY CRITICAL EVALUATIONS, INCLUDING BUT NOT LIMITED TO EVALUATIONS OF LIFE SUPPORT APPLICATIONS.

4.2 User must read and apply the user guide and other available documentation provided by TI regarding the EVM prior to handling or using the EVM, including without limitation any warning or restriction notices. The notices contain important safety information related to, for example, temperatures and voltages.

4.3 *Safety-Related Warnings and Restrictions:*

4.3.1 User shall operate the EVM within TI's recommended specifications and environmental considerations stated in the user guide, other available documentation provided by TI, and any other applicable requirements and employ reasonable and customary safeguards. Exceeding the specified performance ratings and specifications (including but not limited to input and output voltage, current, power, and environmental ranges) for the EVM may cause personal injury or death, or property damage. If there are questions concerning performance ratings and specifications, User should contact a TI field representative prior to connecting interface electronics including input power and intended loads. Any loads applied outside of the specified output range may also result in unintended and/or inaccurate operation and/or possible permanent damage to the EVM and/or interface electronics. Please consult the EVM user guide prior to connecting any load to the EVM output. If there is uncertainty as to the load specification, please contact a TI field representative. During normal operation, even with the inputs and outputs kept within the specified allowable ranges, some circuit components may have elevated case temperatures. These components include but are not limited to linear regulators, switching transistors, pass transistors, current sense resistors, and heat sinks, which can be identified using the information in the associated documentation. When working with the EVM, please be aware that the EVM may become very warm.

4.3.2 EVMs are intended solely for use by technically qualified, professional electronics experts who are familiar with the dangers and application risks associated with handling electrical mechanical components, systems, and subsystems. User assumes all responsibility and liability for proper and safe handling and use of the EVM by User or its employees, affiliates, contractors or designees. User assumes all responsibility and liability to ensure that any interfaces (electronic and/or mechanical) between the EVM and any human body are designed with suitable isolation and means to safely limit accessible leakage currents to minimize the risk of electrical shock hazard. User assumes all responsibility and liability for any improper or unsafe handling or use of the EVM by User or its employees, affiliates, contractors or designees.

4.4 User assumes all responsibility and liability to determine whether the EVM is subject to any applicable international, federal, state, or local laws and regulations related to User's handling and use of the EVM and, if applicable, User assumes all responsibility and liability for compliance in all respects with such laws and regulations. User assumes all responsibility and liability for proper disposal and recycling of the EVM consistent with all applicable international, federal, state, and local requirements.

5. *Accuracy of Information:* To the extent TI provides information on the availability and function of EVMS, TI attempts to be as accurate as possible. However, TI does not warrant the accuracy of EVM descriptions, EVM availability or other information on its websites as accurate, complete, reliable, current, or error-free.

6. *Disclaimers:*

- 6.1 EXCEPT AS SET FORTH ABOVE, EVMS AND ANY WRITTEN DESIGN MATERIALS PROVIDED WITH THE EVM (AND THE DESIGN OF THE EVM ITSELF) ARE PROVIDED "AS IS" AND "WITH ALL FAULTS." TI DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, REGARDING SUCH ITEMS, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER INTELLECTUAL PROPERTY RIGHTS.
- 6.2 EXCEPT FOR THE LIMITED RIGHT TO USE THE EVM SET FORTH HEREIN, NOTHING IN THESE TERMS AND CONDITIONS SHALL BE CONSTRUED AS GRANTING OR CONFERRING ANY RIGHTS BY LICENSE, PATENT, OR ANY OTHER INDUSTRIAL OR INTELLECTUAL PROPERTY RIGHT OF TI, ITS SUPPLIERS/LICENSORS OR ANY OTHER THIRD PARTY, TO USE THE EVM IN ANY FINISHED END-USER OR READY-TO-USE FINAL PRODUCT, OR FOR ANY INVENTION, DISCOVERY OR IMPROVEMENT MADE, CONCEIVED OR ACQUIRED PRIOR TO OR AFTER DELIVERY OF THE EVM.

7. *USER'S INDEMNITY OBLIGATIONS AND REPRESENTATIONS.* USER WILL DEFEND, INDEMNIFY AND HOLD TI, ITS LICENSORS AND THEIR REPRESENTATIVES HARMLESS FROM AND AGAINST ANY AND ALL CLAIMS, DAMAGES, LOSSES, EXPENSES, COSTS AND LIABILITIES (COLLECTIVELY, "CLAIMS") ARISING OUT OF OR IN CONNECTION WITH ANY HANDLING OR USE OF THE EVM THAT IS NOT IN ACCORDANCE WITH THESE TERMS AND CONDITIONS. THIS OBLIGATION SHALL APPLY WHETHER CLAIMS ARISE UNDER STATUTE, REGULATION, OR THE LAW OF TORT, CONTRACT OR ANY OTHER LEGAL THEORY, AND EVEN IF THE EVM FAILS TO PERFORM AS DESCRIBED OR EXPECTED.

8. *Limitations on Damages and Liability:*

- 8.1 *General Limitations.* IN NO EVENT SHALL TI BE LIABLE FOR ANY SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF THESE TERMS AND CONDITIONS OR THE USE OF THE EVMS PROVIDED HEREUNDER, REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. EXCLUDED DAMAGES INCLUDE, BUT ARE NOT LIMITED TO, COST OF REMOVAL OR REINSTALLATION, ANCILLARY COSTS TO THE PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, RETESTING, OUTSIDE COMPUTER TIME, LABOR COSTS, LOSS OF GOODWILL, LOSS OF PROFITS, LOSS OF SAVINGS, LOSS OF USE, LOSS OF DATA, OR BUSINESS INTERRUPTION. NO CLAIM, SUIT OR ACTION SHALL BE BROUGHT AGAINST TI MORE THAN ONE YEAR AFTER THE RELATED CAUSE OF ACTION HAS OCCURRED.
- 8.2 *Specific Limitations.* IN NO EVENT SHALL TI'S AGGREGATE LIABILITY FROM ANY WARRANTY OR OTHER OBLIGATION ARISING OUT OF OR IN CONNECTION WITH THESE TERMS AND CONDITIONS, OR ANY USE OF ANY TI EVM PROVIDED HEREUNDER, EXCEED THE TOTAL AMOUNT PAID TO TI FOR THE PARTICULAR UNITS SOLD UNDER THESE TERMS AND CONDITIONS WITH RESPECT TO WHICH LOSSES OR DAMAGES ARE CLAIMED. THE EXISTENCE OF MORE THAN ONE CLAIM AGAINST THE PARTICULAR UNITS SOLD TO USER UNDER THESE TERMS AND CONDITIONS SHALL NOT ENLARGE OR EXTEND THIS LIMIT.

9. *Return Policy.* Except as otherwise provided, TI does not offer any refunds, returns, or exchanges. Furthermore, no return of EVM(s) will be accepted if the package has been opened and no return of the EVM(s) will be accepted if they are damaged or otherwise not in a resalable condition. If User feels it has been incorrectly charged for the EVM(s) it ordered or that delivery violates the applicable order, User should contact TI. All refunds will be made in full within thirty (30) working days from the return of the components(s), excluding any postage or packaging costs.

10. *Governing Law:* These terms and conditions shall be governed by and interpreted in accordance with the laws of the State of Texas, without reference to conflict-of-laws principles. User agrees that non-exclusive jurisdiction for any dispute arising out of or relating to these terms and conditions lies within courts located in the State of Texas and consents to venue in Dallas County, Texas. Notwithstanding the foregoing, any judgment may be enforced in any United States or foreign court, and TI may seek injunctive relief in any United States or foreign court.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2015, Texas Instruments Incorporated

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com