



1: Click here  
->then open advanced setting window

2: set "0300" & click "Reload"

3: check value here -> it is 0x208

4: Re-plugged Ether cable to generate connection error



Offs	Dec	Hex	Char
0306	0	0000	..
0308	0	0000	..
030a	0	0000	..
030c	85	0055	U.
030e	0	0000	..
0310	520	0208	..
0312	0	0000	..
0314	0	0000	..
0316	0	0000	..
0318	0	0000	..
031a	0	0000	..
031c	0	0000	..
031e	0	0000	..
0320	0	0000	..
0322	0	0000	..
0324	0	0000	..
0326	0	0000	..
0328	0	0000	..
032a	0	0000	..
032c	0	0000	..
032e	0	0000	..
0330	0	0000	..
0332	0	0000	..
0334	0	0000	..
0336	0	0000	..
0338	0	0000	..
033a	0	0000	..
033c	0	0000	..
033e	0	0000	..
0340	0	0000	..
0342	0	0000	..
0344	0	0000	..
0346	0	0000	..
0348	0	0000	..
034a	0	0000	..
034c	0	0000	..
034e	0	0000	..
0350	0	0000	..
0352	0	0000	..
0354	0	0000	..
0356	0	0000	..
0358	0	0000	..
035a	0	0000	..
035c	0	0000	..
035e	0	0000	..
0360	0	0000	..
0362	0	0000	..
0364	0	0000	..
0366	0	0000	..
0368	0	0000	..
036a	0	0000	..
036c	0	0000	..
036e	0	0000	..
0370	0	0000	..
0372	0	0000	..
0374	0	0000	..
0376	0	0000	..
0378	0	0000	..
037a	0	0000	..
037c	0	0000	..
037e	0	0000	..
0380	0	0000	..
0382	0	0000	..
0384	0	0000	..
0386	0	0000	..
0388	0	0000	..
038a	0	0000	..
038c	0	0000	..
038e	0	0000	..
0390	0	0000	..
0392	0	0000	..
0394	0	0000	..
0396	0	0000	..
0398	0	0000	..
039a	0	0000	..
039c	0	0000	..
039e	0	0000	..
03a0	0	0000	..
03a2	0	0000	..
03a4	0	0000	..
03a6	0	0000	..
03a8	0	0000	..
03aa	0	0000	..
03ac	0	0000	..
03ae	0	0000	..
03b0	0	0000	..
03b2	0	0000	..
03b4	0	0000	..
03b6	0	0000	..
03b8	0	0000	..
03ba	0	0000	..
03bc	0	0000	..
03be	0	0000	..
03c0	0	0000	..
03c2	0	0000	..
03c4	0	0000	..
03c6	0	0000	..
03c8	0	0000	..
03ca	0	0000	..
03cc	0	0000	..
03ce	0	0000	..
03d0	0	0000	..
03d2	0	0000	..
03d4	0	0000	..
03d6	0	0000	..
03d8	0	0000	..
03da	0	0000	..
03dc	0	0000	..
03de	0	0000	..
03e0	0	0000	..
03e2	0	0000	..
03e4	0	0000	..
03e6	0	0000	..
03e8	0	0000	..
03ea	0	0000	..
03ec	0	0000	..
03ee	0	0000	..
03f0	0	0000	..
03f2	0	0000	..
03f4	0	0000	..
03f6	0	0000	..
03f8	0	0000	..
03fa	0	0000	..
03fc	0	0000	..
03fe	0	0000	..

5: check again "it is 0x20a"  
[STRANGE: it seems to increment "two"]

Their expectation is only increment "one"