

MTBF Estimate

Device: WL1831MOD (Module)

MTBF (hrs): 5,028,923 FIT: 198.8

Method of Assessment: SR332, Issue3

Temperature: 55C

Environment: Ground Fixed, Uncontrolled

Reference Document: SR-332, Issue 3 - Reliability Prediction Procedure for Electronic Equipment,

Telecordia

Definitions:

Device: TI product part number of product family description

MTBF: Mean Time Between Failures

FIT: Failures-in-Time. The number of failures per 1E9 device-hours

Usage Temp (°C): Estimated usage temperature

THIS INFORMATION IS PROVIDED STRICTLY "AS IS." TI warrants that its products conform to the official published Specifications for such products, in accordance with TI's Terms of Sale at the following link: TERMS OF SALE. Use of TI products outside limits stated in those Specifications is entirely at the customer's risk, and will void the warranty if such misuse causes the part not to work. Quality and reliability data provided by TI, such as MTBF and fit rate data, is intended to facilitate an estimate of the parts performance based on historical observations/industry standard methodologies. It should not be read as indicating that any performance levels reflected in such data can be met if the part is operated outside appropriate conditions or outside the conditions described. Also, the accuracy of any projection is subject to many factors outside TI's control or knowledge; so users should carefully assess predictive value in light of additional factors as appropriate. This information could change without notice. TI makes no warranties and assumes no liability for applications assistance or customer product design. Customers are solely responsible to conduct sufficient engineering and additional qualification testing to determine whether a candidate device is suitable for use in their applications.